- **Multimedia Base (6G3B11)**
  Powerful 36 W PMPO stereo sound output
  Bass Boost for extra enhancement
  Headphone connector for personal listening
  Microphone connector for recording and videoconferencing

- **USB Hub (PCUH411)**
  Connect up to 127 USB devices simultaneously
  1 upstream port and 4 downstream ports
  Self-powered or bus-powered operation
  Fulfills USB-IF specification Rev. 1.1
  Stands alone or clips on monitor base

**Multimedia Base
/USB Hub**

Multimedia Base

USB Hub attached to
standard base

USB Hub attached to
multimedia base

Multimedia Base

Philips Monitors

USB Hub

Let's make things better.

PHILIPS

Product Number 6G3B11 (Multimedia Base)

Technical Specifications

Amplifier
- RMS Power   2x1.5W
- PMPO Power   36 Watts
- Input Signal Level   340 mV RMS
- Bass Boost

Speakers
- Unit Diameter   2"
- Impedance   4Ω
- Frequency Response   140Hz-20kHz
- Dual Passive Bass Pipes

Option
USB Hub PCUH411 Clip-On Option

Adapter
- Input   108~132 VAC, 60Hz, 0.1A (10W)
- Output: 9 VDC, 600mA

Regulatory Approvals
- UL   • CSA
- CE   • TCO '99

Physical Specifications
- Dim. (Excl. Swivel)(WxHxD)(inch)   9.4" x 2.1" x 8.2"
- Dim. (Excl. Swivel)(WxHxD)(mm)   239 mm x 54 mm x 208 mm
- Additional Height for Monitor   1.1"/28 mm
                                        (Multimedia Base-Normal Base)
- Weight   2.0 lbs./0.9 kg
- Additional Weight for Monitor   1.1 lbs./0.5 kg
                                        (Multimedia Base-Normal Base)
- Power Consumption   5 Watts
- UPC Code   0 37849 89587 0 (6G3B11)
- Carton Dimensions (WxHxD)(inch)   12.8" x 9.8" x 4.5"
- Carton Dimensions (WxHxD)(mm)   239 mm x 54 mm x 208 mm
- Carton Weight   3.1 lbs./1.4 kg

Connections and Cables
- Headphone Connection   3.5 mm jack
- Microphone Input   3.5 mm jack
- Microphone Output   3.5 mm jack
- Audio Cable   1.8M, 3.5 mm jack to 3.5 mm jack

Product Number PCUH411 (USB Hub)

Technical Specifications

Device Support
- All USB Products
- Up to 127 Devices Simultaneously

Standards
- USB-IF Specification Rev. 1.1

Bandwidth
- 1.5 Mbps for Unshielded Cable
- 12 Mbps for Shielded Cable

Ports
- 4 Downstream Ports
- 1 Upstream Port

Over-Current Protection
- On Each Downstream Port

Power Source
- Self-Powered via Power Supply
- Bus-Powered from PC
- Maximum per Port Current   500 mA
  (when using power supply)

Power Consumption
- Operating Current   65 mA

Power Supply
- Input   100~240V, 1.0A max.
                              50~60Hz, 28~40VA
- Output   +5V, 2.6A

LED Indicators
- Green/On = Link/Active Port
- Green/Off = Over-Current or Alert

Regulatory Approvals (Version Dependent)
- CE   • CSA   • FCC
- C-Tick   • UL   • T-mark

Environment
- Operation Temperature   0°C to 70°C
- Humidity   0%-80% RH Non-Condensing

Physical Specifications
- Weight   .4 lbs./150g
- Dim. With Cover (WxHxD)(inch)   5.3" x 1.0" x 2.8"
- Dim. With Cover (WxHxD)(mm)   136 mm x 25 mm x 72 mm
- Dim. Without Cover (WxHxD)(inch) 5.3" x 1.0" x 2.1"
- Dim. Without Cover (WxHxD)(mm) 136 mm x 25 mm x 55 mm
- UPC Code   0 37849 89681 5
- Carton Dimensions (WxHxD)(inch) 10.0" x 7.2" x 2.7"
- Carton Dimensions (WxHxD)(mm)   255 mm x 183 mm x 68 mm
- Carton Weight   1.5 lbs./0.7 kg

Compatibility
For Multimedia Base and USB Hub compatibility with monitors, refer to chart below. (The USB Hub can be used stand alone or attached to the 6G3B11 Multimedia Base.)

	105Exx	105Sxx	105Bxx	107Sxx	107Bxx	107Pxx	107Txx	109Sxx	109Bxx	109Pxx	201Bxx	201Pxx
Base		•	•	•	•	•	•	•	•			
Hub	•	•	•	•	•	•	•	•	•	•	•	•

Windows® 95/98/NT is a trademark of Microsoft Corp.
All trademarks acknowledged.

INTERNET ADDRESS: http://www.philipsusa.com
FAX INFORMATION SYSTEM: (865) 521-4341
TECHNICAL SUPPORT: (877) 835-1838 (USA)
                             (903) 242-4804 (outside USA)

Specifications subject to change without notice.

Let's make things better.

PHILIPS